

# ADAPTER-24W

## DESKTOP

### Green Mode

Meet CEC Regulations & RoHS Compliance  
No Load Power Consumption less than 0.5W



### FEATURE

<b>Desktop</b>	IEC 320 / C8
Input Range	90~264 V / 47~63Hz
Output	5V~24V / 1.0A~4.0A (24W max.)
Efficiency	79% min. (Meet CEC)
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
Load Regulation	±5%
Leakage Current	Less than 0.25mA
M.T.B.F.	100,000 hours min. at 25°C, by MIL-HDBK-217F
Cable type	UL2468 / 18 AWG or 20 AWG, Ferrite Core (Option)
Dimension	88(L) x 50(W) x 34(H) mm
Weight	166g (reference)
Application	Broadband & Network Equipment, Wireless Product, Portable Equipment
<b>SAFETY &amp; EMI</b>	
Safety	CB / UL / cUL / PSE / BSMI / GS / RCM / LPS
EMI	RCM, CE/FCC Class B, Conduction & Radiation
<b>ENVIRONMENTAL</b>	
Operating Temperature	0 ~ + 40°C
Storage Temperature	-20 ~ + 60°C
Relative Humidity	(Operating) 20~80% RH (Storage) 10~90% RH

AC Socket (C8): 【 T-Desktop 】

### RULE OF THE MODEL NAME

NO	Model Name	O/P Voltage(V)	O/P Current(A)	PO(W)
1	STD-05040T	5.0	4.0	20.00
2	STD-12020T	12.0	2.0	24.00
3	STD-24010T	24.0	1.0	24.00