



HOME

ABOUT US

NEWS

INQUIRY FORM

CONTACT US

AC-DC adapter

Open Frame

Charger

AC-DC adapter

# ADAPTER-24W

## U.S.A./TAIWAN/JAPAN

**Green Mode**

Meet CEC Regulations &amp; RoHS Compliance



### FEATURE

Wallmount	U.S.A./TAIWAN/JAPAN
Input range	90-264V/47~63Hz
Output	5V~24V/1A~4A(24W max.)
Efficiency	76% typical
Protection	Short circuit protection/Over voltage protection/Over current protection
Load regulation	+5%
Leakage Current	Less than 0.25mA
M.T.B.F.	50,000 hours min. at 25C , full load
Cable type	UL2468/18AWG or 20AWG
Dimension	72X34X52mm
Weight(reference)	175g

### Application

Application            Network equipment, Wireless product , Portable equipment

### Safety & EMI

Safety	UL/cUL/GS/CB/PSE/BSMI
EMI	CE Class B, conduction & Radiation MEET

### Environmental

Operating temperature	0~+40C
Storage Temperature	-20~+60C
Relative Humidity	(operating)20~80%RH/(storage)10~90%RH

### RULE OF THE MODEL NAME

<b>NO</b>	<b>MODEL NAME</b>	<b>Voltage(V)</b>	<b>Current(A)</b>	<b>Power(W)</b>
1	STD-05040U	5	4	20
2	STD-12020U	12	2	24
3	STD-24010U	24	1	24

Copyright © 2007 Adapter Technology Co., Ltd.. All Rights Reserved